



Sulfurization-proof Low Resistance Chip Resistors

Model No.	LCRS10	LCRS16	LCRS20	LCRS32	LCRS35	LCRS50
Size Code inch	0402	0603	0805	1206	1210	2010
Size Code mm	1005	1608	2012	3216	3225	5025

■Features

- Use of special protective material made excellent sulfurization-proof characteristic.
- Both reflow and flow soldering are applicable.
- Superior endurance to heat and environment, due to metal-glaze thick film materials.

■Applications

- Peripheral Circuit of power supply
- Circuit with possibility of causing sulfurization phenomenon

■Model Designation

<p>LCRS16 ①Model No.</p>	↓ hyphen	<p>R47 ②Resistance</p>	<p>J ③Tolerance</p>	<p>V ④Packaging</p>																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><th>①Model No.</th></tr> <tr><td>LCRS10</td></tr> <tr><td>LCRS16</td></tr> <tr><td>LCRS20</td></tr> <tr><td>LCRS32</td></tr> <tr><td>LCRS35</td></tr> <tr><td>LCRS50</td></tr> </table>	①Model No.	LCRS10	LCRS16	LCRS20	LCRS32	LCRS35	LCRS50		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><th>②Resistance</th></tr> <tr><td style="text-align: center;">3 digit (Resistance) (Marking)</td></tr> <tr><td style="text-align: center;">0.47Ω → R47</td></tr> <tr><td style="text-align: center;">No marking on LCRS10</td></tr> </table>	②Resistance	3 digit (Resistance) (Marking)	0.47Ω → R47	No marking on LCRS10	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2">③Tolerance(%)</th></tr> <tr><th>Symbol</th><th>Tolerance</th></tr> <tr><td>F</td><td>± 1</td></tr> <tr><td>G</td><td>± 2</td></tr> <tr><td>J</td><td>± 5</td></tr> </table>	③Tolerance(%)		Symbol	Tolerance	F	± 1	G	± 2	J	± 5	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2">④Packaging</th></tr> <tr><th>Symbol</th><th>Packaging</th></tr> <tr><td>B</td><td>Bulk</td></tr> <tr><td>V</td><td>Paper taping</td></tr> <tr><td>E</td><td>Embossed taping</td></tr> </table>	④Packaging		Symbol	Packaging	B	Bulk	V	Paper taping	E	Embossed taping
①Model No.																																			
LCRS10																																			
LCRS16																																			
LCRS20																																			
LCRS32																																			
LCRS35																																			
LCRS50																																			
②Resistance																																			
3 digit (Resistance) (Marking)																																			
0.47Ω → R47																																			
No marking on LCRS10																																			
③Tolerance(%)																																			
Symbol	Tolerance																																		
F	± 1																																		
G	± 2																																		
J	± 5																																		
④Packaging																																			
Symbol	Packaging																																		
B	Bulk																																		
V	Paper taping																																		
E	Embossed taping																																		

■Rating

Model No.	Rated Wattage (W)	Tolerance (%)		Resistance Range E-24 Series Standard (Ω)	T.C.R. (ppm/°C)
LCRS10	0.100	G	±2	0.20 ~ 0.91	±300
		J	±5		
LCRS16	0.100	G	±2	0.20 ~ 0.91	±300
		J	±5		
LCRS20	0.125	F	±1	0.20 ~ 0.91	±200
		G	±2	0.10 ~ 0.91	
		J	±5		
LCRS32	0.250	F	±1	0.20 ~ 0.91	±100
		G	±2	0.10 ~ 0.91	
		J	±5		
LCRS35	0.500	F	±1	0.20 ~ 0.91	±100
		G	±2	0.10 ~ 0.91	
		J	±5		
LCRS50	0.750	F	±1	0.20 ~ 0.91	±100
		G	±2	0.10 ~ 0.91	
		J	±5		

Operating temperature range : -55 °C ~ +125 °C

■Dimension, Power rating, Packaging

Refer "Dimension, Packaging,etc."