压馬 生 维马克马

Piezoelectric Acoustic Components

独自の積層技術および電極接続技術により、高音圧を実現


Proprietary multilayering technology and electrode connecting technology make possible high sound pressure.

製品構造・量産ラインの一貫設計により、製品設計の自由度が高い

There is a high degree of freedom in product design due to the integrated design of product structure/mass production line.





Simulation analysis design by CAE is possible.



仕様に合わせて設計致します

We will design to your specifications.





ご要求の用途に応じ単板~積層板にて多彩な特性(音圧レベル・周波数) の各種カスタム設計および生産対応可能 Various custom designs and production with a variety of characteristics (sound pressure level, resonance frequency, band, etc.) are possible by using the plates from single to multilayer according to the required application.

SPECIFICATIONS


音圧レベル	共振周波数	帯域	入力電圧	動作温度範囲
Sound Pressure Level	Resonant Frequency	Band	Input Voltage	Operating Temperature Range
60 ∼ 100dB	$1\sim 4$ kHz	$0.1\sim 2$ kHz	Max.30V _{P-P}	

APPLICATION

車載部品 Automotive devices
二輪部品 Motorcycle devices
家電製品 Home appliances

FEATURES

小型、軽量で消費電力が少ない Small and light weight, low power consumption 寿命は半永久的で信頼性が高い



Reliable, perpetual life